

Duplex and Quad Box Power Cord Reels

Model with cord & bumper	Cord Ending	Cord Specifications				Volts	Amps	Shipping Weight		Size Index #
		AWG	mm ²	# Cond	ft m			Type**	lbs	
L 4545 123 7*	Duplex box outlet with GFCI NEMA 5-15R, Inlet straight blade plug NEMA 5-15P	12	3.32	3	45 14	SJE00W	125	15	29 13	1
L 5550 123 7*		12	3.32	3	50 15	SE00W	125	15	45 20	3
L 70075 123 7*		12	3.32	3	75 23	SE00W	125	15	72 33	5
L 4525 123 7A*	Duplex box outlet with GFCI NEMA 5-20R, Inlet straight blade plug NEMA 5-20P	12	3.32	3	25 8	SJE00W	125	20	27 12	1
L 4545 123 7A*		12	3.32	3	45 14	SJE00W	125	20	29 13	1
L 5550 123 7A*		12	3.32	3	50 15	SE00W	125	20	45 20	3
L 70075 123 7A*		12	3.32	3	75 23	SE00W	125	20	72 33	5
L 70100 123 7A*		12	3.32	3	100 30	SE00W	125	20	76 34	5
L 4545 123 7AC*	Duplex box outlet with GFCI NEMA 5-20R, Inlet twist lock plug NEMA L5-20P	12	3.32	3	45 14	SJE00W	125	20	29 13	1
L 4525 123 7B	Duplex box outlet NEMA 5-20R, Inlet straight blade plug NEMA 5-20P	12	3.32	3	25 8	SJE00W	125	20	27 12	1
L 4545 123 7B		12	3.32	3	45 14	SJE00W	125	20	29 13	1
L 5550 123 7B		12	3.32	3	50 15	SE00W	125	20	45 20	3
L 4525 123 7BC	Duplex box outlet NEMA 5-20R, Inlet twist lock plug NEMA L5-20P	12	3.32	3	25 8	SJE00W	125	20	27 12	1
L 4525 123 7P	Quad box outlet NEMA 5-15R, Inlet straight blade plug NEMA 5-15P	12	3.32	3	25 8	SJE00W	125	15	27 12	1
L 5550 123 7P		12	3.32	3	50 15	SJE00W	125	15	45 20	3
L 4525 123 7Q	Quad box outlet NEMA 5-20R, Inlet straight blade plug NEMA 5-20P	12	3.32	3	25 8	SJE00W	125	20	27 12	1
L 4545 123 7Q		12	3.32	3	45 14	SJE00W	125	20	29 13	1
L 5550 123 7Q		12	3.32	3	50 15	SJE00W	125	20	45 20	3
L 4525 123 7QC	Quad box outlet NEMA 5-20R, Inlet twist lock plug NEMA L5-20P	12	3.32	3	25 8	SJE00W	125	20	27 12	1
L 4545 123 7QC		12	3.32	3	45 14	SJE00W	125	20	29 13	1
L 70100 123 7QC		12	3.32	3	100 30	SE00W	125	20	76 34	5

For indoor non-weathertight applications only. All models UL listed at 125 Volt 60 HZ single phase. Swing brackets or pivot bases should be used if cords are pulled at more than 45°, see page 43. *The GFCI Receptacle is designed to protect from line-to-ground shock hazards. It does not protect against short circuits or overloads; this is the function of the fuse or circuit breaker. **Equivelant cord type may be used.



L 4545 123 7



Cord End Specifications

	#7 - Duplex Outlet Box 15 AMP duplex outlet box with GFCI protection. Includes flip cover. NEMA 5-15R
	#7A/7AC/7B/7BC - Duplex Outlet Box 20 AMP duplex outlet box. GFCI protection on #7A/7AC. Includes flip cover. NEMA 5-20R
	#7P - Quad Box 15 AMP quad outlet box. Four receptacles. Does not include flip cover. NEMA 5-15R
	#7Q/7QC - Quad Box 20 AMP quad outlet box. Four receptacles. Does not include flip cover. NEMA 5-20R



Reverse Plug Power Cord Reels

Model with cord & bumper	Cord Ending	Cord Specifications				Volts	Amps	Shipping Weight		Size Index #
		AWG	mm ²	# Cond.	ft m			Type**	lbs	
L 4035 163 3-RP	Outlet straight blade plug NEMA 5-15P, Inlet single receptacle NEMA 5-15R	16	1.33	3	35 11	SJE00W	125	13	26 12	1
L 4050 163 3-RP		16	1.33	3	50 15	SJE00W	125	13	29 13	1
L 4545 123 3A-RP	Outlet straight blade plug NEMA 5-20P, Inlet single receptacle NEMA 5-20R	12	3.32	3	45 14	SJE00W	125	20	28 13	1
L 70100 123 3A-RP		12	3.32	3	100 30	SE00W	125	20	74 34	5
L 5750 103 4	RV plug NEMA TT-30P outlet, Flying lead inlet	10	5.37	3	50 15	SO0W	125	30	50 23	4


For indoor non-weathertight applications only. All models UL listed at 125 Volt 60 HZ single phase. Swing brackets or pivot bases should be used if cords are pulled at more than 45°, see page 43. **Equivelant cord type may be used.



L 4050 163 3-RP

Ideal for mobile applications, including carts

Reverse Plug



Refer to page 32 for dimensional drawings for all cord reels.