

Hand Crank Reels

Up to 150' fuel gas
Up to 100' 8/3 cable

- Designed for manual winding of air/water/fuel gas hose, electric cord, and welding cable
- Ideal for applications where space, weight, and flexibility are key
- Offer trouble-free management of large capacities of hose or cord
- Glass-filled nylon spools are very strong and durable while ensuring that no conductivity occurs
- A substantial welded aluminum base is used to support the weight of the spool



Dimensions - Size Index									
Diagram	1		Diagram	2		Diagram	3		
	in	mm		in	mm		in	mm	
	A	38	965		38	965		19	483
	B	18	457		18	457		18	457
	C	6	152		6	152		6	152
	D	6 1/2	165		6 1/2	165		6 1/2	165
	E	16 1/4	737		16 1/4	737		29	737

Four 1/2" (12.7 mm) diameter mounting holes

Model without hose	Hose I.D.		Hose O.D.		Reel Capacity		Pressure		Shipping Weight		Size Index #
	in	mm	in	mm	ft	m	psi	bar	lbs	kg	
Single Spool Oxygen/Acetylene T-Grade Seals					Maximum temperature 150 °F (65 °C)						
T-1225-04	1/4	6	.530	13	150	45	200	14	19	9	1
T-1225-04-100T*	1/4	6	.530	13	100	30	200	14	44	20	1
T-1226-06	3/8	10	.625	16	100	30	200	14	19	9	1

*Includes hose.


Model without cable	Cable Size						Cable / Hose Capacity	Volts	Amps	Shipping Weight		Size Index #	
	#1 (42 mm²)		1/0 (54 mm²)		2/0 (67 mm²)					lbs	kg		
	ft	m	ft	m	ft	m	ft	m					
Single Welding Cable													
T-1460-0	250	76	200	61	200	61	-----	600	300	32	15	1	
Dual Side-by-Side Welding Cable (2)													
T-2462-0	250	76	200	61	200	61	-----	600	250	51	23	3	
Dual Stacked Welding Cable (2)													
T-2464-0	250	76	200	61	200	61	-----	600	250	62	28	2	
Dual Side-by-Side Power Cable/Air Hose													
T-2735-2-0*	---	---	---	---	---	---	200/150	61/45	600	33	40	18	3

For indoor non-weathertight applications only. *Air hose side has 1/2" (12.7mm) inlet.

Caution: Compressed air hoses should not be converted to oxygen service. Compressed air hoses are often contaminated with an oil coating, which can react explosively when oxygen is introduced. Oxygen/Acetylene cannot be combined with welding cable or power cord. **Note:** Safe-T-Reels are available with cable or hose and in various combinations. Please consult Reelcraft customer service for additional information.

Detail of heavy duty shaft
with tapered roller bearing for high rigidity

Shaft sizes are 1" to 1.25" in diameter, supported by tapered roller bearings with 2" to 2.3" housings.



T-1225-04-100T



Interactive Reel Catalog

Visit reelcraft.com/catalog for complete product specifications, parts, and accessories.



Inlet & Outlet Welding Hoses
See page 36